







Model	AVL-IDT6	AVL-ID4	AVL-ID5	AVL-ID6	AVL-ID8V	AVL-ID8
LED Pixel Arrangement and Layout of Pixels						
Pixel Pitch	6mm	8mm	10mm	12mm	16mm	16mm
LED Configuration	3 in 1 (SMD)	2R,1G,1B (SMD)	2R,1G,1B (SMD)	2R,1G,1B (SMD)	2R,1G,1B (SMD)	2R,1G,1B (Lamp)
Brightness	1,500 cd/m ² (or 3,000 cd/m ²)	3,000 cd/m ²	2,000 cd/m ²	1,500 cd/m ²	1,500 cd/m ²	3,000 cd/m ²
Viewing Angle(H/V)	160/160	160/160	160/160	160/160	160/160	130/60
Pixel Density	27,777/m ²	15,625/m ²	9,687/m ²	6,944/m ²	3,906/m ²	3,906/m ²
One Module Area (sq.m)	0.29	0.26	0.42	0.59	0.52	0.52
Size(H×W×D) mm	384×768×150 (4H X 4W L/U)	512×512×150 (2H X 2W L/U)	650×650×120 (2H X 2W L/U)	768×768×120 (2H X 2W L/U)	1024×512×150 (4H X 2W L/U)	1024×512×150 (4H X 2W L/U)
Approx. Mass (kg)	20	19	24	35	35	35
Outline (mm)	